

**STUDIES OF PRIMARY MICROWAVE FREQUENCY CONVERTERS BASED ON THE MEASURING CELL WITH RECTANGULAR WINDOW**

The goal of this work is to estimate the effect of the dielectric properties, shape, and geometric dimensions of inserts in a rectangular window of a waveguide meter thick-walled diaphragm on the reflection and transmission coefficients. The estimation of the effects of the geometric dimensions, forms and dielectric properties of the material for partial filling the measuring waveguide cell on its resonance properties has been simulated on the computer. The method of partial domains has been chosen as an apparatus for modeling. The form of the sample of partial dielectric filling for meters with a rectangular window of an insert was demonstrated to affect the frequency characteristics of the measuring cell. Dielectric samples in the form of a parallelepiped may increase the sensitivity of primary microwave frequency converters in comparison with cylindrical samples. A limiting cross-section area for materials under consideration may not exceed  $7 \text{ mm}^2$ .

**Keywords:** *super high frequencies, thick-walled diaphragm, waveguide, coefficients of reflection and transmission, relative dielectric constant.*

1. Evanescent-mode bandpass filters based on ridged waveguide sections and inductive strips / A. Kirilenko, L. Rud, V. Tkachenko, D. Kulik // IEEE MTT-S, Microwave Symposium Digest. – 2001. – Vol. 2. – P. 1317 – 1320.
2. Craven G. F. Waveguide band-pass filters using vanescent modes / G. F. Craven // Electron. Lett. – 1966. – Vol. 2, No 7. – P. 251 – 252.
3. Shestopalov V. P. Resonance Wave Scattering. Vol. 2. Waveguide Non-Uniformities (in Russian) / V. P. Shestopalov, A. A. Kirilenko, L. A. Rud. – Kiev : Naukova Dumka, 1986. – 216 p.
4. Computational Methods for Modern Radio Physics: Book (in Russian) / V. F. Kravchenko, O. S. Labunko, A. M. Lerer, G. P. Sinyavsky. – Moscow : FIZMATLIT, 2009. – 469 p.